

Con-pro

Con-pro Teflon Hose, Polypropylene Braid

Helically convoluted, self cleaning PTFE hose with Polypropylene over braid. Polypropylene over braid is preferred where weight reduction and operator handling are considerations.

Internal Wire reinforcement is optional to provide greater vacuum resistance and kink resistance. Please note that the Maximum Operating Temperature is 90°C. Assemblies are supplied accordance with pressure Equipment

Regulations SI 1999 No. 2001 and Pressure Equipment Directive 97/23/EC.



Description	ID (mm)		Wall Thickness (mm)	OD (mm)		Min. Bend Radius (mm)	Max. Working Pressure (Bar)	Min. Burst Pressure (Bar)	Vacuum (Torr)
	(Min.)	(Max.)		(Min.)	(Max.)				
1/2"	11.6	13.6	0.89	21.4	23.4	50	10	40	710
210	15.1	16.4	0.89	26.3	28.2	65	10	40	710
3/4"	19.5	20.5	1	31.1	33.9	55	10	40	710
1"	24.5	25.5	1.1	36.7	40.7	85	10	40	710
1 1/4"	31.5	32.5	1.15	44.4	48.6	100	10	40	710
1 1/2"	36.5	37.5	1.45	49.7	52.4	120	10	40	710
1 3/4"	44.5	45.5	1.45	58.3	63.9	135	10	40	710
2"	49.5	50.5	1.5	62.5	69.2	165	10	40	710
2 1/2"	62.5	63.5	1.6	83.4	91.6	230	7	28	710
3"	73.5	74.5	1.6	92.9	102.2	260	6	24	710

