



Pacific Hoseflex

PTY LTD



F-Swivel



Due to the wide range of flanges and materials, each swivel joint is made to order.

- Strong Body
- Short and long body versions
- Clean internal body
- No Intrusions to upset flow
- Same size through body
- Different sizes for different situations
- Different end pieces as required
- Easy to service
- Internal bearing to keep stress off seals and longer life
- No snap rings or circlips to break

Code	Description
150# - 038 ^{^^} - ** - _ - F	1 1/2"
200# - 050 ^{^^} - ** - _ - F	2"
250# - 065 ^{^^} - ** - _ - F	2 1/2"
300# - 075 ^{^^} - ** - _ - F	3"
400# - 100 ^{^^} - ** - _ - F	4"
500# - 125 ^{^^} - ** - _ - F	5"
600# - 150 ^{^^} - ** - _ - F	6"
800# - 200 ^{^^} - ** - _ - F	8"

LEGEND-

: B= BSP, N= NPT, J= JIC, M= Metric, BW= Butt-weld, SW= Socket-weld, A= ANSI (state class), TE= Table 'E', TD= Table 'D', TF= Table 'F', TH= Table 'H', D= DIN 16, C= Custom

X : F= Female, M= Male, FL= Flange

* : SS= Stainless Steel, CS= Carbon Steel, PP= Polypropylene, PT= PTFE

_ : E= EPDM, P= PTFE, N= Neoprene, B= Buna Nitrile, V= Viton

^ = OAL Requested

**** Custom design and larger sizes available on request ****