

2.15 | Stripwound Stainless & Galvanised Metal Hose

Light weight Engine Exhaust

Typical applications include commercial vehicle, passenger vehicle plus plant and portable generator set exhaust systems. This is a general purpose flexible metallic light weight conduit designed for a variety of installations requiring motion, vibration and bending.

ID (mm)	OD (mm)	Bend radius (mm)
19	22.0	140
25	28.0	152
32	36.0	160
38	41.3	166
41	44.3	180
44	47.3	190
48	51.3	195
51	54.3	205
57	60.3	235
63	66.3	260
70	73.3	285
76	79.3	205

ID (mm)	OD (mm)	Bend radius (mm)
90	94.2	250
102	106.2	370
114	118.2	490
127	131.2	515
140	144.2	600
152	156.2	655
178	183.0	740
203	208.0	800
230	234.0	950
254	259.0	1100
305	310.0	1400
355	360.0	1500

Flexible Electrical Conduit

These products are designed to provide shielding for electrical cables. It gives additional protection against crushing, incandescent projection of rubber hose, electrical cables, heat insulation, and exposure to water, oils and other fluids. On request the hose is available in a PVC cover.

I.D (mm)	O.D (mm)	Bend radius (mm)
6.4	11.7	25
10.0	14.7	25
12.5	18.0	38
16.0	21.0	50
21.0	26.5	64
26.5	33.0	75
35.0	42.0	89
40.5	48.0	114
51.5	60.0	140
78.5	88.0	254
101.0	114.0	305